

Major Process Tank Information

Tank #	Description	Length (Ft)	Width (Ft)	Depth (Ft)	Volume (cu Ft)	Volume (Gal)	Rectifier size (amps)	Notes
9	Chromic Anodize	15	4.0	6.0	360.0	2689.2	3000	
11	Hard Anodize	15	4.0	6.0	360.0	2689.2	2000	
12	Sulfuric Anodize	15	4.0	6.0	360.0	2689.2	2000	
12'	Boric Sulfuric Anodize	15	4.0	6.0	360.0	2689.2	2000	Waiting on first order for Boeing approval
53	Alodine 1200	15	3.0	5.1	228.8	1708.8		
102	Passivation ty VI	2.3	0.0	3.4	29.8	222.7		
105	Passivation ty II	2.3	3.4	3.9	30.1	224.9		
134	Manganese Phosphate	2.3	2.0	2.8	13.2	98.8		
TBD	Black Oxide(Cold)		2.3	3.4	29.8	222.7	n/a	
141	Hard Anodize	6.8	2.1	3.9	55.8	416.5	750	
174	Caustic Etch	2.4	5.9	3.9	56.0	418.3		
211	LHE cad	6.6	2.4	3.7	58.3	435.8	1000	
215	Bright cad	5.9	2.4	4.4	63.2	471.7	1000	
251	Tin	2.4	5.5	3.4	44.9	335.3	1000	
253	Nickel strike	2.4	2.9	2.7	18.8	140.4	100	
264	Electroless Nickel	1.5	2.8	1.8	7.6	56.5		
300	Copper strike	2	2.8	2.8	15.1	113.0	100	
302	Silver Plate	1.8	1.8	2.0	6.7	50.2	250	
G1	Aurobond Gold Plating	0.9	1.3	1.0	1.1	8.6	30	
G2	E56 Gold Plating	1.1	1.6	1.1	1.9	13.9	30	
G3	Pur A Gold Plating	1	1.3	1.0	1.3	10.0	30	
DPC1	IVD #1	10.0	5.0	1.2				
DPC2	IVD #2	10.0	5.0	1.2				Barrel Coater Attachment
DPC3	IVD #3	8.0	4.0	4.0				Barrel Coater
DPC4	IVD #4	10.0	5.0	1.2				Barrel Coater Attachment